

SV-E60

CE  E60




2009.77 (eng)

Fire-resistant vertically sliding window

Fire-resistant, vertically sliding, electrically operated window which is suitable for indoor or outdoor installation. The sliding window has a frame made in powder coated steel. The SV-E60 model is specially designed for installations in which demands are made on fire resistance class E15-E60 and it is provided with 6 mm Pyran S fire resistant glass. It is automatically locked in closed position and at 50 mm intervals across the opening. Operated by control switch with hold to run buttons. S3 control system is optional.



DESIGN



Window with
one sliding
section

TECHNICAL INFORMATION

NAME	SV-E60
DESCRIPTION	Fire-resistant, vertically sliding, electrically operated window for indoor or outdoor installation.
WIDTH	600 - 1165 mm.
HEIGHT	800 - 2100 mm.
FRAME THICKNESS	80 mm.
WIDTH SIDE POSTS	60 mm.
HEIGHT TOP PROFILE	70 mm.
HEIGHT OF BOTTOM PROFILE	U-profile 25 x 25 x 25 mm.
GLASS FRAMES	40 mm.
CONSTRUCTION	Motor, transmission and automatic locking are integrated within the frame.
LOCKING	Mechanical lock which automatically locks the window in closed position and at 50 mm intervals across the opening.
POWER SUPPLY	230 V AC transformer. Options: battery backup.
CONTROL SYSTEM	Electromechanical control system with hold to run buttons. Options: S3 control system (with soft start/stop, adjustable speed, optional push-and-release buttons, optional alarm closing, etc) and various control switches.
GLASS	6 mm Pyran S, fire resistance classification E60.
SURFACE COATING	Powder coating in white is standard. Powder coating in other RAL-colours are optional.
PROTECTION AGAINST FIRE	Fire resistance classification E60. The sliding window is certified by SITAC. Please contact our sales personnel for country specific information.
MANUFACTURED BY	Svalson AB, Sweden

Visit www.svalson.com for more information.

Design and material subject to change without prior notice.

